

www.projectcollection.co.uk

5
YEAR
warranty

2024



project

collection

by searchlight

ceiling / recessed / recessed plaster / track & spot / led strip / wall reading lights / wall / wall plaster / table & floor / shades / outdoor /

CI/SfB (63)X

2024

project

collection


the 2024 Project Collection is a toolkit solution for lighting specifiers. Tailored to align with project requirements, it optimises lighting outcomes with architectural design, empowering informed decisions, and maximising efficiency. Streamline your specifications and achieve outstanding project outcomes with our collection.

useful information

GU10 items

All GU10 products are designed to be compatible with a standard GU10 lamp length of 53mm. The minimum recess depth dimensions specified for our products are based on this standard lamp length of 53mm, providing a clear guideline for installation. Where items are designed for use with a longer GU10 lamp length this is indicated in the key features on the product page.

GU10 lamps are not included.



Dimming

All dimmable products are compatible with mains leading and/or trailing edge dimming. We test all our dimmable products for compatibility with Varilight Pro-dimmer modules. We cannot guarantee the compatibility of other leading / trailing edge dimmers.



Products with this icon are limited stock items.

Colour Rendering Index (CRI)

All products have a minimum CRI >80. CRI>90 products are indicated on the page.

Photometric files

Where possible, we provide LDT/IES data for our products to facilitate the generation of lighting plans to ensure seamless integration into your projects. These are available to download from our product pages at...

www.projectcollection.co.uk

We can further assist in the generation of effective lighting designs for your projects. Whether you need guidance on product selection, positioning, or other aspects of lighting planning.

Power Factor

Every product in our range delivers a minimum power factor of 0.9, unless otherwise specified.

Warranty

All products are manufactured and inspected in order to meet the technical and quality standards demanded by the market. These come with a standard 5 year warranty out of the box.



















We understand that coastal environments can subject products to unique challenges, such as saltwater exposure and extreme weather conditions, our 5 year warranty includes all outdoor products with this icon, when used in locations up to 1km from the coast.



Scan here for further help & advice.



contents
ceiling

<p>13 New</p> 	<p>14-15 New</p> 	<p>16-17 New</p> 	<p>18-19 New</p> 
<p>laser pendant</p>	<p>vistina round</p>	<p>vistina long</p>	<p>lino 2</p>
<p>20-21 New</p> 		<p>22-23</p> 	<p>24-25</p> 
<p>ara 60cm / 100cm / 150cm</p>		<p>orbit 120cm</p>	<p>compass 2m</p>
<p>28</p> 		<p>26</p> 	<p>27</p> 
<p>clip</p>	<p>vulcan 2ft / 4ft</p>	<p>eternity 78cm</p>	<p>eternity 55cm</p>
<p>29</p> 		<p>30-31 New</p> 	
<p>vulcan 2ft / 4ft</p>		<p>verve 💧</p>	<p>32 New</p> 
<p>33</p> 	<p>34-35 New</p> 		<p>36</p> 
<p>peri 30cm 💧</p>	<p>orcus / saturn</p>		<p>andaman 💧</p>
<p>37</p> 		<p>37</p> 	
<p>banda 💧</p>		<p>banda 💧</p>	

38-39

New



swivel / andromeda

40-41



honos

42



lyra

43



artemis / apollo

recessed

46-47

New



moon recessed

48-49

New



polo

50-51

New



mini

52-53



wall washers

54-55



grid WW / WB / BB



56-57



slim FR 🔥

58



slim trim adjustable FR 🔥

59



slim trim adjustable

60



slim trim IP65 FR 🔥💧

61



slim trim IP65 💧

62



glacier IP65 💧

63

New



sophie IP65 💧

64-65



slim trimless FR 🔥

contents
recessed

66-67

New



sablons

70-71



plaster downlights

72-73



solid plaster wall lights

74-76



metal trimless wall lights

77-79



recessed IP wall lights

80-81



marker lights

track
& spot

84-91

New



track, track heads and accessories

92

New



laser spot

93



selene

94-97



moon

98-99



jupiter


led strip

102-105



led strip / IP65

106-109



aluminium profile and drivers

contents

wall

112-113

New



blackfrairs

114

New



perla

115

New



laser reader

116

New



marlow 

117

New



dalston

118



ice

119

New



marylebone

120-121




victoria LED / recessed 

122-123



mini projector

124-125



sloane

126



shoreditch

127



southwark

128-129



vavin

130-131



london bridge

132-133



halkin

134-137



pimlico (2) / reader

138-139



victoria / reader

140



fenchurch

144



concorde


145



europe

contents
wall plaster

146-147



mirabeau / monceau

148



avron

149



cadet

150



cambronne

151



opera / odeon

mirror

216



acqua

table
& floor

154-155



156-157



158-159



libra 2

olympia

kensington

shades

162-164



shades

165



3-light

contents outdoor

168-169



euston / hood

170-171



plot light

172



piccadilly

173



paddington

174-175



farringdon / plus

176



beaumont

177



sanderson

178



grosvenor

179



grosvenor II

180-181



connaught / plus

182-184



lanesborough / savoy

185



berkeley

186-187



strand / mayfair

189



trafalgar

190-191



kobe / kyoto

192-193




chiba duo / tokyo

194-195



yokhama

196-197



sapporo / suzuka



For detailed drawings and specifications along with help & advice, visit www.projectcollection.co.uk



ceiling

New



See pages below for the rest of the laser family:

- laser GU10 track 87
- laser spot 92
- laser reader 115



PE-LAS6-B

PE-LAS6-W


laser pendant

New

PE-LAS6-B



PE-LAS6-W



CLASS 2



DIMMABLE



ANTI-GLARE

Key Features

Sand black / Sand white

Aluminium / Frosted diffuser

GU10 max. 10W LED only

Min. drop: 200mm

90° pivot, 350° rotation

New



PE-VISTR-B



3000K

4000K



PE-VISTR-W



Transformative optic

vistina round

New

PE-VISTR-B ■


4550 lumens at 4000K

4300 lumens at 3000K

PE-VISTR-W □

4900 lumens at 4000K

4650 lumens at 3000K



Transformative optic
(clear when off, opaque
when on)



CLASS 1



DIMMABLE



CCT

2 COLOURS

3000K

4000K

Key Features

Sand black / Sand white

Aluminium / Acrylic

3000K / 4000K Switchable

Switch in ceiling can

42W SMD LED

Min. drop: 400mm

New



PE-VIST-W





PE-VIST-B



Adjustable suspension cable

Min. suspension spacing (a) : 720mm
Max. suspension spacing (b) : 1020mm





PE-VIST-W

vistina long


New

PE-VIST-B ■

5100 lumens at 4000K
4750 lumens at 3000K

PE-VIST-W □

5700 lumens at 4000K
5250 lumens at 3000K



Transformative optic
(clear when off, opaque
when on)



CLASS 1



DIMMABLE



Key Features

Sand black / Sand white

Aluminium / Acrylic

3000K / 4000K Switchable

Switch in ceiling can

50W SMD LED

Min. drop: 300mm



CE-LINO2-B



CE-LINO2-W



CE-LINO2-W

lino 2 pendant / flush

CE-LINO2-B ■

3850 lumens at 4000K
3650 lumens at 3000K

CE-LINO2-W □

3900 lumens at 4000K
3700 lumens at 3000K



CLASS 1



DIMMABLE



Key Features

Sand black / Sand white

Aluminium / Polycarbonate


3000K / 4000K switchable

Switch in body of fitting

37W SMD LED direct (down only)

Min. drop: 150mm

Includes flush mounting kit



New





PE-ARA100-W

PE-ARA60-B

ara 60cm

PE-ARA60-B ■
 2400 lumens at 4000K
 2250 lumens at 3000K

PE-ARA60-W □
 2500 lumens at 4000K
 2300 lumens at 3000K

ara 100cm

PE-ARA100-B ■
 5200 lumens at 4000K
 4900 lumens at 3000K

PE-ARA100-W □
 5700 lumens at 4000K
 5400 lumens at 3000K

ara 150cm



PE-ARA150-B ■
 6800 lumens at 4000K
 6300 lumens at 3000K


PE-ARA150-W □
 8300 lumens at 4000K
 7800 lumens at 3000K



New





PE-ARA150-B



CLASS 1



DIMMABLE

CCT
2 COLOURS
 3000K
 4000K

Key Features

Sand black / Sand white

Aluminium / Acrylic

3000K / 4000K Switchable

Switch in ceiling can

Min. drop: 400 / 500 / 750mm

Flush alternative: see pg. 34



PE-ORB120-BS



PE-ORB120-WS



PE-ORB120-BS

illuminated
inside ring





PE-ORB120-BS

orbit 120cm

PE-ORB120-BS ■
3200 lumens at 4000K
3000 lumens at 3000K

PE-ORB120-WS □
4200 lumens at 4000K
3800 lumens at 3000K



CLASS 1



DIMMABLE



Key Features

Sand black / Sand white

Aluminium / Silicone diffuser

3000K / 4000K Switchable

Switch in ceiling can

69W SMD LED

Min. drop: 900mm

White ceiling can



PE-COM2-BS



PE-COM2-WS



PE-COM2-BS





PE-COM2-WS

Direct (downwards) illumination

compass 2m

PE-COM2-BS ■
 4800 lumens at 4000K
 4300 lumens at 3000K

PE-COM2-WS □
 6000 lumens at 4000K
 5500 lumens at 3000K



CLASS 1



Key Features

Sand black / Sand white

Aluminium / Opal polycarbonate

3000K / 4000K Switchable

Switch in ceiling can

102W SMD LED

Min. drop: 900mm

White ceiling can




PE-E7E78-B



3000K



4000K




Cross section showing light direction

eternity 78cm pendant

PE-E7E78-B
3600 lumens



PE-E7E78
4700 lumens



PE-E7E78-



CLASS 1



DIMMABLE

Key Features

Sand black / Sand white

Aluminium / Polycarbonate

diffuser

3000K

85W SMD LED

Min. drop: 700mm



PE-ETE55-BS



FL-ETE55-WS




FL-ETE55-WS

eternity 55cm pendant


PE-ETE55-BS ■
 2450 lumens at 4000K
 2100 lumens at 3000K

PE-ETE55 □
 2500 lumens
 at 3000K



eternity 55cm flush


FL-ETE55-WS □
 2000 lumens at 3000K
 2200 lumens at 4000K



CLASS 1



DIMMABLE



Key Features

- Sand black / Sand white
- Aluminium / Polycarbonate diffuser
- 3000K or 4000K, switched in ceiling can (-BS/-WS version only)
- 39W SMD LED
- Min. drop: 450mm
- Ceiling or wall mounted (flush only)




PE-CLIP



PE-CLIP

clip pendant

PE-CLIP
2650 lumens



CLASS 1



DIMMABLE

Key Features

Sand white

Aluminium / Acrylic

3000K

43W SMD LED

Min. drop: 350mm



AM-VUL4



AM-VUL2

AM-VUL4

vulcan 2ft

AM-VUL2

18W SMD LED
1700 lumens

vulcan 4ft

AM-VUL4 ▲

36W SMD LED
3000 lumens



CLASS 2

Key Features

Opal / Aluminium body /

White end caps


Aluminium / Polycarbonate

3000K

Ceiling or wall mounted




CE-VER40-W



+



=



CE-VER(30/40)

PA-VER

verve 30cm IP44

New


- CE-VER30-B
- CE-VER30-W

16W SMD LED
 1450 lumens at 3000K
 1750 lumens at 4000K
 1650 lumens at 5700K

suspension kit IP20

- PA-VER-B
- PA-VER-W

New



verve 40cm IP44

New

- CE-VER40-B
- CE-VER40-W

23W SMD LED
 2100 lumens at 3000K
 2300 lumens at 4000K
 2100 lumens at 5700K



CLASS 2



DIMMABLE



IP 44

CCT

3 COLOURS

3000K

4000K

5700K

Key Features

Sand black / Sand white

Aluminium / PC diffuser

3000K / 4000K / 5700K

Switchable

Switch on back of fitting

Rear or side cable entry

Ceiling or wall mounted

Add PA-VER to suspend from

200mm up to 2m, n.b. IP20



3000K



4000K



5700K



CE-VER30-B & PA-VER-B




ripple 40cm



FL-RPL40


2350 lumens at 3000K
2450 lumens at 4000K



CLASS 1



DIMMABLE



Key Features

Sand white

Steel / Acrylic

3000K / 4000K switchable

CCT switch in body of fitting

25W SMD LED

Ceiling or wall mounted



CE-PER130



peri 30cm IP54


New

CE-PER130

1400 lumens at 3000K

1800 lumens at 4000K

1600 lumens at 5000K



CLASS 2



DIMMABLE



IP
54



Key Features

White

Polycarbonate

3000K / 4000K / 5000K switchable

CCT switch in body

17W SMD LED

Rear or side cable entry

Ceiling or wall mounted



CE-ORC40



FL-SAT40-W




3000K

4000K


saturn 60cm

- FL-SAT60-W ▲
- 2500 lumens
- FL-SAT60-WS*
- 53W SMD LED



saturn 40cm

- FL-SAT40-W ▲
- 3700 lumens
- FL-SAT40-WS*
- 38W SMD LED



CLASS 1



DIMMABLE



Key Features

Matt white / Frosted

Steel / Acrylic diffuser

3000K or 4000K, switch in body
(-WS version only)

*For lumen output, see website



Ceiling or wall mounted

New

orcus 40cm

New

CE-ORC40
1750 lumens



CE-ORC40



CLASS 1



DIMMABLE

Key Features

Matt white / Clear

Steel / Acrylic diffuser

3000K

23W SMD LED

Ceiling or wall mounted



FL-ADM40-W




FL-ADM40-W

FL-ADM30-W


andaman 40cm IP44

FL-ADM40-W
25W SMD LED
1200 lumens



andaman 30cm IP44

FL-ADM30-W
14W SMD LED
600 lumens



CLASS 2



DIMMABLE



IP
44



GLASS

Key Features

Clear glass / Matt white inner glass

Glass / Steel

3000K

Ceiling or wall mounted




FL-BAN35-B



FL-BAN23-B


**banda 35cm
IP44**

FL-BAN35-B ■
27W SMD LED
650 lumens



**banda 23cm
IP44**

FL-BAN23-B ■
14W SMD LED
350 lumens



CLASS 2



DIMMABLE



IP 44



GLASS

Key Features

Matt white glass / Black

Glass / Steel

3000K



CE-SWI-W



CE-SWI-W

Shown at 90°



CE-SWI-B

New



swivel

New

CE-SWI-B



CE-SWI-W



Simultaneous 90° pivot and rotation



andromeda ceiling



ANTI-GLARE


CE-AND-B



CE-AND-W



90° pivot, 350° rotation



CLASS 2




DIMMABLE

Key Features

Sand black / Sand white

Aluminium


GU10 max. 10W LED only



honos square twin

CE-HONSQ2W

2 x GU10





CE-HONSQ2W



CE-HONRB



CE-HONSQW



CE-HONSQB



CE-HONSQW

honos round

- CE-HONRB
- CE-HONRW
- 1 x GU10

honos square

- CE-HONSQB
- CE-HONSQW
- 1 x GU10

- 
CLASS 2
- 
DIMMABLE
- 
ANTI-GLARE



Key Features

Sand black / Sand white

Aluminium

GU10 max. 10W LED only


20° tilt, 360° rotation






lyra pendant

PE-LYRAB  
895 lumens



lyra flush

FL-LYRAB  
895 lumens




Key Features

- Sand black / gold interior
- Aluminium
- 3000K
- 10W CREE COB LED
- Min. drop: 200mm (pendant only.)




artemis GU10 pendant

PE-ART-B
PE-ART-W



apollo GU10 pendant

PE-APO-B
PE-APO-W



CLASS 1



DIMMABLE



TRACK
ADAPTER

Key Features

Sand black / Sand white

Steel

GU10 max. 10W LED only

Min. drop: 200mm

Compatible with pendant track
adapter



Compatible with
pendant track adapter



For detailed drawings and specifications along with help & advice, visit www.projectcollection.co.uk



recessed



See Pg. 94-97 for
the rest of the Moon
product range




Retrofit

Suitable for installation into
downlight holes Ø60-Ø85mm

**moon
recessed**



- SP-MOOR-B ■
- SP-MOOR-W □



Key Features

- Sand white or Sand black
- GU10 LED only / Max. 10W
- 350° Rotation
- 90° Pivot

New



DL-POLW



PL-POLW



PL-POLW



DL-POLW



PL-POLW




polo

New

DL-POLW



CUT OUT 92mm
MIN DEPTH 135mm



polo trimless


New

PL-POLW



CUT OUT 92mm
MIN DEPTH 135mm

Ceiling must be skimmed after installation



CLASS 2 DIMMABLE

Key Features

Sand white

Aluminium


GU10 Max. 10W LED only

90° pivot, 350° rotation

Use in any position from fully recessed to fully extended

Distance to front of lamp : 12mm

New



PL-MINW



PL-MINW



DL-MINW



Size comparison:
PL-SLIMW (left) vs PL-MINW (right)
See pg. 64 for PL-SLIMW


What is a GU11?



mini



DL-MINW




mini trimless



PL-MINW



Ceiling must be skimmed
after installation



Key Features

Sand white

Aluminium

GU11 Max. 10W LED only

30° tilt, 360° rotation

Distance to front of lamp: 30mm



GU10 wall washer


DL-WWW



CUT OUT
85mm



MIN DEPTH
112mm



CLASS 2



DIMMABLE

Key Features

Matt white

Die cast aluminium

1 x GU10, max. 10W, LED only


60° tilt



DL-WASH



DL-WASH



LED wall washer

DL-WASH




650 lumens



CUT OUT
76mm



MIN DEPTH
100mm



CLASS 2



DIMMABLE

Key Features

Sand white

Aluminium

3000K

9W COB LED

40° tilt, 350° rotation


Mains dimmable driver included

Tilt angle locked by screw if
required



grid 1

- DL-GRID1BB ■
- DL-GRID1WB ▣
- DL-GRID1WW □



CLASS 2



DIMMABLE

Key Features

Matt black / Matt white & black /
Matt white

Aluminium

GU10 Max. 10W LED only

15° tilt, 360° rotation

Distance to front of lamp: 30mm



DL-GRID3WW



DL-GRID3WB



DL-GRID3BB



DL-GRID2WW



DL-GRID2WB



DL-GRID2BB


grid 3

- DL-GRID3BB
- DL-GRID3WB
- DL-GRID3WW



grid 2

- DL-GRID2WW
- DL-GRID2WB
- DL-GRID2BB



Key Features

- Matt black / Matt white & black / Matt white
- Aluminium
- GU10 Max. 10W LED only
- 15° tilt, 360° rotation
- Distance to front of lamp: 30mm



DL-GRID2FRWB 🔥



DL-GRID2FRWB 🔥

FIRE RATED 🔥



DL-GRID2FRWB 🔥



DL-GRID1FRWW 🔥

grid 1 FR




- DL-GRID1FRWW
- DL-GRID1FRWB



grid 2 FR



- DL-GRID2FRWW
- DL-GRID2FRWB
- DL-GRID2FRBB



Key Features

Matt black / Matt white & black /
Matt white

Steel

GU10 Max. 10W LED only

15° tilt, 360° rotation

Distance to front of lamp: 30mm

Tested in 30, 60 and 90 minute


ceilings



grid 1 FR trimless



PL-GRID1FR 



Key Features

Matt white

Steel


GU10 Max. 10W LED only

15° tilt, 360° rotation

Ceiling must be skimmed after installation

Distance to front of lamp: 26mm

Tested in 30, 60 and 90 minute ceilings



DL-SLIMFRW

slim trim adjustable FR




DL-SLIMFRW



CUT OUT
84mm



MIN DEPTH
133mm



DL-SLIMFRW



CLASS 1



DIMMABLE

Key Features

Matt white

Steel

GU10 Max. 10W LED only

20° tilt

Distance to front of lamp: 33mm

Tested in 30, 60 and 90 minute ceilings



DL-SLIMW



DL-SLIMB

DL-SLIMW



DL-SLIMSQW



DL-SLIMSQB

DL-SLIMSQW

slim trim adjustable

DL-SLIMB




DL-SLIMW



CUT OUT
83mm



MIN DEPTH
145mm



slim trim square adjustable

DL-SLIMSQB




DL-SLIMSQW



CUT OUT
78 x 78mm



MIN DEPTH
135mm



CLASS 2



DIMMABLE

Key Features

Matt black / Matt white

Aluminium

GU10 Max. 10W LED only

45° tilt

Distance to front of lamp: 32mm



Products with this icon are limited stock items.



DL-SLIMFRW 


FIRE RATED

slim trim
IP65 FR




DL-SLIMIPFRW 



CUT OUT
72mm



MIN DEPTH
120mm



DL-SLIMIPFRW  



CLASS 1



DIMMABLE



IP
65

Key Features

Matt white

Steel

1 x GU10, max 10W LED only

Anti-glare

GU10 lampholder

Tested in 30, 60 and 90 minute
ceilings

Distance to front of lamp: 26mm



DL-SLIMIPW



DL-SLIMIPB

DL-SLIMIPW

slim trim IP65

DL-SLIMIPB ■


DL-SLIMIPW □



CUT OUT
70mm



MIN DEPTH
135mm



CLASS 2



DIMMABLE



IP
65

Key Features

Matt black / Matt white

Aluminium

1 x GU10, Max. 10W LED only

Lamp change from the front,
mounting sleeve remains in the
ceiling

Distance to front of lamp: 27mm



DL-GLAR




DL-GLAR

glacier round IP65

DL-GLAR  



CUT OUT
70mm



CLASS 2

DIMMABLE

IP
65

Key Features

Acrylic & Polished chrome

1 x GU10, max. 10W LED only



DL-SOPWB



DL-SOPWB



DL-SOPWB

sophie IP65

New


DL-SOPWB □ / ■



CUT OUT
65mm



MIN DEPTH
120mm



CLASS 2



DIMMABLE



IP
65

Key Features

Matt White

1 x GU10, max. 10W LED only

Suitable for indoor or
outdoor use

Comes with both black and white
covers in the box


Distance to front of lamp: 6mm



PL-SLIMW



PL-SLIMIPW



PL-SLIMW

slim trimless IP65


PL-SLIMIPW



CUT OUT
85mm



MIN DEPTH
140mm



slim trimless adjustable

PL-SLIMW


20° tilt



CUT OUT
80mm



MIN DEPTH
140mm



CLASS 2



DIMMABLE



ANTI-GLARE

Key Features

Sand white

Aluminium

GU10 Max. 10W LED only

Ceiling must be skimmed after
installation

Distance to front of lamp: 30mm



PL-SLIMFRW 


**slim trimless
adjustable FR**



PL-SLIMFRW



CUT OUT 85mm
MIN DEPTH 148mm



PL-SLIMFRW 



CLASS 1 DIMMABLE ANTI-GLARE

Key Features

Matt white

Steel

GU10 Max. 10W LED only

20° tilt


Ceiling must be skimmed after installation

Fire rated: Tested in 30, 60 and 90 minute ceilings

Distance to front of lamp: 35mm



PL-SAB1-B



PL-SAB1-W



PL-SAB1-B



PL-SAB2-W



New

PL-SAB2-W



PL-SAB2-W




PL-SAB1-B

sablons 1 trimless

New


- PL-SAB1-B
- PL-SAB1-W



sablons 2 trimless

New

- PL-SAB2-B
- PL-SAB2-W



- CLASS 1
- DIMMABLE

Key Features


- Sand black / Sand white
- Aluminium
- GU10 Max. 10W LED only
- 45° gimbal
- Ceiling must be skimmed after installation
- Distance to front of lamp: 17mm

Choose solid plaster trimless lighting...

where you have an already plastered wall or ceiling, and you're not planning to skim the surface again.

After the product installed it is a decorators job to infill the gap with a flexible filler / caulk, sand to a smooth finish and paint the surface including the interior of the fitting.

installing solid plaster trimless lighting




Choose metal trimless lighting...

where you are installing into a wall or ceiling that has yet to be skimmed, or will be reskimmed.

After the metal frame is installed in the wall or ceiling the plasterer skims the surface with a 3mm layer of plaster skim. The frames have a 3mm lip for the plasterer to skim up to.

installing metal frame trimless lighting



See pages below for our metal frame trimless ranges

Ceiling

Polo plaster	49
Mini plaster	51
Grid plaster fire-rated	57
Slim trimless	64-65
Sablons	67

Wall

Boulogne LED	74-75
Blanche LED	74-75
Blanche GU10	76





PL-ROM2




PL-ROM1 / PL-ROM2



PL-ROM2


rome

PL-ROM1 



rome 2

PL-ROM2 



Key Features


White plaster

GU10, max. 10W LED only

How to fit guide - see website

If skimming the ceiling, complete this before installing

 This symbol represents a white plaster finish




PL-TROCA

PL-TROCA

trocadero adjustable

PL-TROCA 

Tilt angle: 40°



CLASS 1 DIMMABLE PAINTABLE ANTI-GLARE

Key Features

White plaster

1 x GU10, max. 10W LED only

How to fit guide - see website

If skimming the ceiling, complete this before installing

 This symbol represents a white plaster finish



pyrenees plaster

Item no.	Finish	Power	CCT	Lumens	Dimmable	Replaceable LED module
PL-PYREN	<input type="checkbox"/> White plaster	350mA	3000K ●	60	Dimmable*	MOD1W
PL-PYREN27	<input type="checkbox"/> White plaster	350mA	2700K ●	60	Dimmable*	MOD1W2700

simplon plaster

Item no.	Finish	Power	CCT	Lumens	Dimmable	Replaceable LED module
PL-SIMPL	<input type="checkbox"/> White plaster	350mA	3000K ●	60	Dimmable*	MOD1W
PL-SIMPL27	<input type="checkbox"/> White plaster	350mA	2700K ●	60	Dimmable*	MOD1W2700

* Dimmable when used with a dimmable driver



PL-SIMPL



PL-SIMPL




PL-SIMPL27



PL-SIMPL


pyrenees plaster

1W CREE XPE Power LED
95 lumens / 30° beam angle



simplon plaster

1W CREE XPE Power LED
95 lumens / 30° beam angle



Key Features

- White plaster
- Driver supplied separately
- Dimmable when used with a dimmable driver
- Not suitable for use in solid walls
- How to fit guide - see website
- If skimming the wall, complete this before installing
- Suitable for plasterboard thickness 9-15mm





boulogne LED

Item no.	Finish	Power	CCT	Lumens	Dimmable	Replaceable LED module
PL-BOU	<input type="checkbox"/> White plaster	350mA	3000K ●	60	Dimmable*	MOD1W
PL-BOU27	<input type="checkbox"/> White plaster	350mA	2700K ●	60	Dimmable*	MOD1W2700

blanche LED


Item no.	Finish	Power	CCT	Lumens	Dimmable	Replaceable LED module
PL-BLA	<input type="checkbox"/> White plaster	350mA	3000K ●	60	Dimmable*	MOD1W
PL-BLA27	<input type="checkbox"/> White plaster	350mA	2700K ●	60	Dimmable*	MOD1W2700

*Dimmable when used with a dimmable driver




boulogne LED

1W CREE XPE Power LED
95 lumens / 30° beam angle



blanche LED

1W CREE XPE Power LED
95 lumens / 30° beam angle



Key Features


- Matt white / Steel
- Driver supplied separately
- Dimmable when used with a dimmable driver
- Not suitable for use in solid walls
- Wall must be skimmed after installation



PL-BLAGU10

**blanche
GU10**

PL-BLAGU10



CLASS 2 DIMMABLE ANTI-GLARE 230 VOLTS

Key Features

- Matt white
- Steel
- 1 x GU10, Max.10W LED only
- Not suitable for use in solid walls
- Wall must be skimmed after installation



IPR-WSLW

IPR-WSLB


Item no.	Finish	Power	CCT	Lumens	IP Rating	Dimmable	Replaceable LED module	Class
IPR-WSLB	■ Black	350mA	3000K	45	65	Yes*	MOD1WIP	III
IPR-WSLB-AC	■ Black	220 - 240V**	3000K	45	65	No	MOD1WIP230V	I
IPR-WSLB27	■ Black	350mA	2700K	45	65	Yes*	MOD1WIP-2700	III
IPR-WSLB27-AC	■ Black	220 - 240V**	2700K	45	65	No	MOD1WIP230V-2700	I
IPR-WSLW	□ White	350mA	3000K	95	65	Yes*	MOD1WIP	III
IPR-WSLW-AC	□ White	220 - 240V**	3000K	95	65	No	MOD1WIP230V	I
IPR-WSLW27	□ White	350mA	2700K	95	65	Yes*	MOD1WIP-2700	III
IPR-WSLW27-AC	□ White	220 - 240V**	2700K	95	65	No	MOD1WIP230V-2700	I

*Dimmable when used with a dimmable driver ** Integrated Driver

simplon IP65

1W CREE XPE Power LED

95 lumens / 30° beam angle



Key Features

Sand white / Sand black

Aluminium

Mounting box included for solid wall applications



IPR-WRW


IPR-WRB

Item no.	Finish	Power	CCT	Lumens	IP Rating	Dimmable	Replaceable LED module	Class
IPR-WRB	■ Black	350mA	3000K	● 50	65	Yes*	MOD1WIP	III
IPR-WRB-AC	■ Black	220 - 240V**	3000K	● 50	65	No	MOD1WIP230V	I
IPR-WRB27	■ Black	350mA	2700K	● 50	65	Yes*	MOD1WIP-2700	III
IPR-WRB27-AC	■ Black	220 - 240V**	2700K	● 50	65	No	MOD1WIP230V-2700	I
IPR-WRW	□ White	350mA	3000K	● 95	65	Yes*	MOD1WIP	III
IPR-WRW-AC	□ White	220 - 240V**	3000K	● 95	65	No	MOD1WIP230V	I
IPR-WRW27	□ White	350mA	2700K	● 95	65	Yes*	MOD1WIP-2700	III
IPR-WRW27-AC	□ White	220 - 240V**	2700K	● 95	65	No	MOD1WIP230V-2700	I

*Dimmable when used with a dimmable driver ** Integrated Driver

pyrenees IP65

1W CREE XPE Power LED
95 lumens / 30° beam angle



Key Features

- Sand white / Sand black
- Aluminium
- Mounting sleeve included for solid wall applications






holborn IP65

IPR-HOLSS


1W CREE XPE Power LED
90 lumens / 120° beam angle



hoxton IP65

IPR-HOXSS ▲ IPR-HOXCP

1W CREE XPE Power LED
90 lumens / 120° beam angle



CLASS 3



IP 65



DIMMABLE



350mA

Key Features

Polished chrome or satin
stainless steel 316 / Aluminium
body
3000K
Very shallow profile
Driver supplied separately
Fittings must be wired in series



IPR-HOLSS


holborn anti glare IP65



IPR-HOLSSAG



IPR-HOLSSAG



Key Features


- Satin stainless steel 316
- 1W CREE XPE / 3000K
- 25 lumens / Beam angle: 120°
- Very shallow profile
- Driver supplied separately
- Fittings must be wired in series

diana



DL-DIA-W

DL-DIA-W



Key Features

- Sand white finish / Die cast body
- 1W Olsen LED / 3000K
- 95 lumens / Beam angle: 30°
- Driver supplied separately
- Fittings must be wired in series



For detailed drawings and specifications along
with help & advice, visit www.projectcollection.co.uk

track & spot






TR-AND-W

TR-AND-B

andromeda GU10 track spot

- TR-AND-B
- TR-AND-W



- 
CLASS 2
- 
DIMMABLE
- 
SWITCH

Key Features

Sand white / Sand black

Aluminium

1 x GU10, max. 10W LED only

350° Rotation / 90° Tilt

On/Off switch on track connector

Suitable for use with longer lamp lengths

New



10W / 12W / 15W



CCT and power switches within body



TR-TAU-W



TR-TAU-B



taurus LED track spot

New

- TR-TAU-B
- TR-TAU-W

1350 lumens at 4000K, 15W
1150 lumens at 3000K, 15W

Taurus is supplied with a default setting of 3000K, 15W



Key Features

- Sand white / Sand black
- Power switchable 10W, 12W, 15W
- 2 CCT Switchable 3000K / 4000K
- On/Off switch on track connector
- Switches located in body of fitting, see image above
- 350° Rotation / 90° Tilt
- CRI>90



TR-LIB-WW



TR-LIB-B



TR-ORI-W

libra GU10 track spot

- TR-LIB-B
- TR-LIB-WW

orion GU10 track spot

- TR-ORI-B
- TR-ORI-W

-  CLASS 2
-  DIMMABLE
-  SWITCH

Key Features


Sand black / Sand white

Aluminium

1 x GU10, max. 10W LED only

350° Rotation / 90° Tilt

On/Off switch on track connector



New



TR-ORI-B



TR-LAS-W



TR-LAS-B

laser GU10 track spot

New

- TR-LAS-B
- TR-LAS-W

-  CLASS 2
-  DIMMABLE
-  SWITCH

Key Features


Sand black / Sand white

Aluminium

1 x GU10, max. 10W LED only

350° Rotation / 90° Tilt

On/Off switch on track connector



See pages below for the rest of the laser family:

laser pendant	13
laser spot	92
laser reader	115



Pick your pendant...

project
collection
searchlight



TR-PEN-B

Scan here to view a wide selection of pendants




TR-PEN-W

Our pendant track adapter allows you to suspend pendants of your choosing to complement and enhance your track lighting scheme. Add pendants over a kitchen island, hotel reception desk or restaurant tables to allow your design ideas to come to life.



* For a detailed guide- see our Help & Advice section on our website



Scan here for further help & advice.




All compatible pendants are marked with this symbol

pendant track adapter

- TR-PEN-B ■
- TR-PEN-W □

Use with any 220-240V pendant under 2kg that is suspended by a single power cable




TR-PEN-B

-  CLASS 1
-  DIMMABLE
-  230 VOLTS

Key Features

Used to convert mains voltage pendants meeting the following criteria:

1. Suspended by a single power cable
2. Maximum 2kg weight

 All compatible pendants are marked with this symbol



TR-1W / TR-1B

1m track kit

- TR-1B
- TR-1W

Includes live end & end cap
L1000 x W35 x H18mm

1m track only

- TR-T1-B
- TR-T2-W

L1000 x W35 x H18mm

2m track kit

- TR-2B
- TR-2W

Includes live end & end cap
L2000 x W35 x H18mm

2m track only

- TR-T2-B
- TR-T2-W

L2000 x W35 x H18mm



CLASS 1 DIMMABLE 230 VOLTS

Key Features

- Extensive range of track & connectors
- Ideal for applications where fittings need to be moved or added
- Earth on the neutral side
- Track can be cut to any length



TR-EC-W



TR-LE-W



TR-MJ-W



TR-XC-W



TR-LC-W



TR-TC-W



TR-SUS-W



TR-CC-W



TR-FC-W

New

end cap

- TR-EC-B
- TR-EC-W

live end

- TR-LE-B
- TR-LE-W

mini joiner

- TR-MJ-B
- TR-MJ-W

X connector

- TR-XC-B
- TR-XC-W

L connector

- TR-LC-B
- TR-LC-W

T connector

- TR-TC-B
- TR-TC-W

3m suspension kit

- TR-SUS-B
- TR-SUS-W

centre connector

- TR-CC-B
- TR-CC-W

flexible connector

- TR-FC-B
- TR-FC-W

- CLASS 1
- DIMMABLE
- 230 VOLTS

Key Features

- Extensive range of track & connectors
- Power feed in with any connector marked
- Earth on the neutral side
- Suspension kit length is adjustable
- See our website for dimensions

New



SP-LAS1S-W



SP-LAS1S-W



SP-LAS1S-B



SP-LAS1S-B

laser spot

New

- SP-LAS1S-B
- SP-LAS1S-W



Key Features

Sand black / Sand white


Aluminium

1 x GU10, max. 10W LED only


Switch on front face

350° rotation, 90° pivot

See pages below for the rest of the laser family:



- laser pendant 13
- laser GU10 track 87
- laser reader 115



- 
 CLASS 2
- 
 DIMMABLE
- 
 IP 44
- 
 GLASS

Key Features

- Sand white / Sand black
- Aluminium
- 3 x GU10, max. 10W LED only
- Ceiling / Wall mounted
- 350° Rotation
- 90° Pivot



SP-SEL3L-W




SP-SEL3L-B



selene 3 round IP44




- SP-SEL3R-B
- SP-SEL3R-W




selene 3 long IP44



- SP-SEL3L-B
- SP-SEL3L-W





DIMMABLE

Key Features

Sand white / Sand black

Aluminium

GU10 LED only, max. 10W each

Ceiling / Wall mounted

350° Rotation

90° Pivot


See pg. 46-47 for full moon

recessed specification




moon 1

- SP-MOO1-B
- SP-MOO1-W
- SP-MOO1S-B*
- SP-MOO1S-W*
- 1 x GU10 LED
- Class I
- *Switched




moon 1 round

- SP-MOO1R-B
- SP-MOO1R-W
- 1 x GU10 LED
- Class I



moon recessed

- SP-MOOR-B
- SP-MOOR-W
- 1 x GU10 LED
- Class II





SP-MOO3-W





SP-MOO3L-W

moon 3

SP-MOO3-B ■
 SP-MOO3-W □
 3 x GU10 LED

moon 3 bar

SP-MOO3L-B ■
 SP-MOO3L-W □
 3 x GU10 LED





SP-MOO3L-B / SP-MOO4-B



SP-MOO2-W


SP-MOO4-W

moon 4 bar

SP-MOO4-B ■
 SP-MOO4-W □
 4 x GU10 LED

moon 2 bar

SP-MOO2-B ■
 SP-MOO2-W □
 2 x GU10 LED



CLASS 1 DIMMABLE

Key Features

- Sand white / Sand black
- Aluminium
- GU10 LED only, max. 10W each
- Ceiling / Wall mounted
- 350° Rotation
- 90° Pivot





SP-JUP1-W



SP-JUP2-B




SP-JUP1-B



SP-JUP2-W


jupiter 1

SP-JUP1-B
 SP-JUP1-W
 1 x ES111



jupiter 2

SP-JUP2-B
 SP-JUP2-W
 2 x ES111



CLASS 1 DIMMABLE

Key Features

Sand black / Sand white

Steel / Aluminium

Ceiling / Wall mounted

350° Rotation

120° Pivot



For detailed drawings and specifications along with help & advice, visit www.projectcollection.co.uk

led strip

guide to using LED strip

① choose your strip and connectors

- 4.8W/m - feature glow of light
- 14.4W/m - ambient light

② choose your colour temperature

- Cool White is 4000K ●
- Warm White is 3000K ●

③ choose your profile

- Recessed profiles conceal lines of light
- Surface mounted profiles are easy to fit
- Use corner profile for angling the strip at 45° to a surface, particularly useful for lighting shelves, inside wardrobes and over kitchen worktops
- A profile must be used with 14.4W/m strips

④ select your driver

- Multiply the total number of metres of strip to be run from a single driver by the wattage of the strip and then add 10% e.g. 16m of 4.8W/m strip plus 10% = 85W
- Decide if your circuit needs to be dimmable
- Select the driver e.g. dimmable LST-DRD120, non-dimmable LST-DR100



LST-4-3-IP / LST-4-3



LST-CON3



LST-CON4

Driver:
Supplied separately



4.8w/m LED strip IP65



90 lumens per Watt

- LST-5-3-IP ● 3000K
- LST-5-4-IP ● 4000K

4.8w/m LED strip

83 lumens per Watt

- LST-5-3 ● 3000K
- LST-4-4 ● 4000K



CLASS 3



DIMMABLE



24 VOLTS

Key Features

5 metre roll

CRI Ra>80

3528 Epistar SMD LED

2oz double sided PCB for longer strip runs

Power feed-in required every 10m

Cut distance every 100mm

Supplied with 150mm tails on both ends



8mm inline connector

LST-CON3



8mm corner connector / power feed in

LST-CON4
2 x Wire





LST-14-3-IP / LST-14-3



LST-CON1



LST-CON2

Driver:
Supplied separately



14.4w/m LED strip IP65



90 lumens per Watt

LST-14-3-IP ● 3000K

LST-14-4-IP ● 4000K

14.4w/m LED strip

100 lumens per Watt

LST-14-3 ● 3000K

LST-14-4 ● 4000K



CLASS 3



DIMMABLE



24 VOLTS

Key Features

5 metre roll

CRI Ra>80

2835 Epistar SMD LED

2oz double sided PCB for longer strip runs

Power feed-in required every 10m

Cut distance every 100mm

Supplied with 150mm tails on both ends



10mm inline connector

LST-CON1



10mm corner connector / power feed in

LST-CON2

2 x Wire





LST-PRO-PL1



LST-PRO-R1



LST-PRO-HS



LST-PRO-PL1

recessed aluminium profile

LST-PRO-R1

L1000 x W25 x H16mm

aluminium heat sink




LST-PRO-HS

L1000 x W25 x H8mm

plastered in profile

LST-PRO-PL1

L1000 x W55.5 x H15mm





LST-PRO-SM1




LST-PRO-COR

surface mounted aluminium profile

LST-PRO-SM1


L1000 x W17.2 x H15mm



45° corner profile

LST-PRO-COR

L1000 x W18.1 x H18.1mm



Key Features

Aluminium / Opal PC diffuser

Includes 2 x End caps

2 x Installation clips with surface profile



LST-DRD200



LST-DRD150



LST-DRD120

LED drivers - dimmable

INPUT POWER
+/-220-250V

MAINS
DIMMER



DIMMING
SYSTEM



MAINS
DIM DRIVER



LED STRIP

LED STRIP

TRIAC dimmable 24v 200w driver

LST-DRD200

TRIAC dimmable 24v 150w driver

LST-DRD150

TRIAC dimmable 24v 120w driver

LST-DRD120



IP
66



DIMMABLE



24 VOLTS

Key Features

PWM Output

Loading: 1-100%

Short circuit protection

TRIAC Dimmable

Dimming range: 0-100%

Leading and trailing edge

Lutron & Clipsal C-BUS compatible



LST-DR150



LST-DR100



LST-DR75



LST-DR50



LST-DR20

LED drivers - non dimmable

INPUT POWER
+/-220-250V

ON/OFF



LED 24v 150w driver

LST-DR150

LED 24v 100w driver

LST-DR100

LED 24v 75w driver

LST-DR75

LED 24v 50w driver

LST-DR50

LED 24v 20w driver

LST-DR20



CLASS 2



24 VOLTS

Key Features

Loading: 1-100%

Over load, short circuit and thermal protection



For detailed drawings and specifications along with help & advice, visit www.projectcollection.co.uk



Wall



WL-BLF-B



WL-BLF-W



blackfriars


New

WL-BLF-B ■

350 lumens

WL-BLF-W □

350 lumens



CLASS 2



SWITCH



FINGERPRINT
RESISTANT

Key Features

Matt black / Sand white

Aluminium / Steel

3000K

4W Bridgelux COB LED

Arm pivots 180°

Head rotates 350° and pivots 90°

New



New



perla

New


WL-PRL-B



WL-PRL-W



WL-PRL-B



CLASS 2



DIMMABLE



SWITCH

Key Features

Sand black / Sand white

Aluminium

GU10 Max. 10W LED only


350° backplate rotation

180° head pivot

New



WL-LASR-W



WL-LASR-B



WL-LASR-B




WL-LASR-W

laser reader

New

WL-LASR-B ■
Backlight: 390 lumens

WL-LASR-W □
Backlight: 660 lumens



See pages below for the laser range:

laser pendant	13
laser GU10 track	87
laser spot	92



CLASS 2 SWITCH

Key Features

Sand black / Sand white

Aluminium / Steel

3000K

Backlight: 7W SMD LED

GU10 Max. 10W LED only

90° pivot, 350° rotation

New



WL-MLW-W



WL-MLW-B




marlow usb

New

WL-MLW-B
300 lumens



WL-MLW-W
330 lumens



CLASS 2



SWITCH



FINGERPRINT
RESISTANT



USB

Key Features

Matt black / Sand white

Aluminium / Steel


3000K

4W Bridgelux COB LED

90° pivot, 350° rotation

2.1 amp USB A and USB C

New



WL-DAL-W

WL-DAL-B

dalston

New

WL-DAL-B



380 lumens


Backlight: 380 lumens

WL-DAL-W



380 lumens

Backlight: 380 lumens



CLASS 2



SWITCH



FINGERPRINT
RESISTANT

Key Features

Matt black / Sand white

Aluminium / Steel

3000K

Backlight: 5W SMD LED

Spot: 4W Bridgelux COB LED

90° pivot, 350° rotation



WL-ICE-B




WL-ICE-W

ice

- WL-ICE-B
- WL-ICE-W

Backlight: 280 lumens
 Reading light: 170 lumens



CLASS 1



SWITCH

Key Features

Sand black / Sand white

Steel / Acrylic

3000K

8.5W SMD LED

3W Power LED

90° pivot, 350° rotation


New



Light off in closed position



WL-MAR-B



WL-MAR-SN



**marylebone
recessed**

New

WL-MAR-B



320 lumens


WL-MAR-SN



320 lumens



CUT OUT
127mm x 40mm



CLASS 1



SWITCH



FINGERPRINT
RESISTANT

Key Features

Matt black / Satin nickel

Steel / Aluminium

3500K

5W Bridgelux COB LED

90° pivot, 350° rotation

Contact switch - off in the closed position



FINGERPRINT
RESISTANT
MATT BLACK



SH-VICLED-MB




SH-VICLED-AB



SH-VICLED-SN

victoria LED

- SH-VICLED-AB ■ ▲
- SH-VICLED-SN ■
- SH-VICLED-MB ■



CLASS 1



SWITCH

Key Features

Matt black / Satin nickel /

Antique brass

Steel / Aluminium

3000K

1W CREE XPE Power LED

90 lumens

90° pivot, 350° rotation




SH-VICLEDR-MB



SH-VICLEDR-MB

victoria LED recessed

SH-VICLEDR-MB ■



CLASS 1



SWITCH



NON-FINGER PRINTING

Key Features

Matt black

Steel / Aluminium

3000K

1W CREE Power LED

90 lumens

90° pivot, 350° rotation





LED-PROJ1W-W



LED-PROJ1W-B




LED-PROJ1W-B



Driver supplied separately, see pg. 220

mini projector

- LED-PROJ1W-B
 - LED-PROJ1W-W
- 90 lumens



CLASS 3



DIMMABLE



350mA

Key Features

Matt black / Matt white

Aluminium

3000K

1W CREE XPE Power LED

360° rotation, 270° pivot

Dimmable when used with a dimmable driver



WL-SLO2-W


sloane 2

WL-SLO2-B ■

500 lumens

WL-SLO2-W □

525 lumens



WL-SLO2-B



CLASS 1



DIMMABLE

Key Features

Sand black / Sand white

Aluminium

3000K

6W Power LED

See pg. 111 to view collection



WL-SLO1-B



WL-SLO1-B



WL-SLO1-W


sloane 1

WL-SLO1-B ■

260 lumens

WL-SLO1-W □

270 lumens



CLASS 1



DIMMABLE

Key Features

Sand black / Sand white

Aluminium

3000K

4W Power LED

See pg. 111 to view collection



WL-SHO20-B

WL-SHO20-W


shoreditch

WL-SHO20-B ■ ▲

555 lumens

WL-SHO20-W □ ▲

1040 lumens



WL-SHO20-B



CLASS 1



DIMMABLE

Key Features

Sand black / Sand white

Aluminium


3000K

17W SMD LED

Can be fitted vertically or

horizontally

See pg. 111 to view collection



WL-SOU24-W



WL-SOU24-B

WL-SOU24-W



WL-SOU24-B


southwark

WL-SOU24-B ■

350 lumens

WL-SOU24-W □

720 lumens



CLASS 1



DIMMABLE

Key Features


Sand black / Sand white

Aluminium

3000K

12W SMD LED

See pg. 111 to view collection



vavin 60

WL-VAV60
 16W SMD LED
 600 lumens



vavin 90

WL-VAV90
 20W SMD LED
 850 lumens



vavin 120

WL-VAV120
 35W SMD LED
 1250 lumens



Key Features

- Sand white
- Aluminium
- 3000K
- Can be fitted vertically or horizontally







WL-LB10



WL-LB20



WL-LB38



WL-LB38



WL-LB20

london bridge

WL-LB10



WL-LB20



WL-LB38



7W POWER LED
450 lumens

7W SMD LED
600 lumens

13W SMD LED
1050 lumens




CLASS 1

Key Features

Sand white

3000K

Can be fitted vertically or horizontally







WL-HALK

WL-HALKB



WL-HALKB



WL-HALK



WL-HALKB

halkin

WL-HALKB ■
230 lumens

WL-HALK □
450 lumens



CLASS 1



SWITCH

Key Features


Sand black / Sand white

Aluminium

3000K

7W SMD LED

350° Rotation





SH-WBPIM-CP & SH-DR15-C



SH-WBPIM-AB



SH-WBPIM-SN




SH-WBPIM-MB

pimlico

- SH-WBPIM-AB ▲
- SH-WBPIM-CP ▲
- SH-WBPIM-SN ▲
- SH-WBPIM-MB ▲

Shades supplied separately,
see pg.162-164



CLASS 1



SWITCH

Key Features

Matt black / Satin nickel /

Antique brass / Polished chrome

Steel

E27 LED Max. 20W



SH-WBPIM2-SN & SH-DR15-C



SH-WBPIM2-CP



SH-WBPIM2-SN




SH-WBPIM2-MB

pimlico 2

New

- SH-WBPIM2-AB
- SH-WBPIM2-CP
- SH-WBPIM2-SN
- SH-WBPIM2-MB

Shades supplied separately,
see pg.162-164



CLASS 1



SWITCH

Key Features

Matt black / Satin nickel /

Antique brass / Polished chrome

Steel

E27 LED Max. 20W

Switch on the front of the product



SH-WBPIMR-CP



SH-WBPIMR-SN



SH-WBPIMR-MB

FINGERPRINT
RESISTANT




SH-WBPIMR-SN & SH-RS-C

pimlico reader

- SH-WBPIMR-AB
- SH-WBPIMR-CP
- SH-WBPIMR-SN
- SH-WBPIMR-MB

Shades supplied separately,
see pg.162-164



CLASS 1



SWITCH

Key Features

Matt black / Satin nickel /
Antique brass / Polished chrome
Steel

E27 LED Max. 20W

Reading Arm

3000K
1W CREE XPE Power LED
90 lumens
Replaceable LED 'MOD1W'



SH-WBPIM2R-CP



SH-WBPIM2R-SN



SH-WBPIM2R-MB




SH-WBPIM2R-CP & SH-SQO-C

pimlico 2 reader

New

- SH-WBPIM2R-AB
- SH-WBPIM2R-CP
- SH-WBPIM2R-SN
- SH-WBPIM2R-MB

Shades supplied separately,
see pg.162-164



CLASS 1



SWITCH

Key Features

Matt black / Satin nickel /
Antique brass / Polished chrome
Steel

E27 LED Max. 20W

Switches on the front of product

Reading Arm

3000K

1W CREE XPE Power LED

90 lumens

Replaceable LED 'MOD1W'



SH-WBVIC-AB



SH-WBVIC-MB



SH-WBVIC-SN




SH-WBVIC-AB & SH-SQO-C



Shades supplied separately, see pg.162-164

victoria

- SH-WBVIC-AB ■
- SH-WBVIC-SN ■
- SH-WBVIC-MB ■



CLASS 1



DIMMABLE



SWITCH

Key Features

Matt black / Satin nickel /

Antique brass

Steel

E27 LED Max. 20W



SH-WBVICR-AB



FINGERPRINT RESISTANT

SH-WBVICR-MB



SH-WBVICR-MB




SH-WBVICR-SN & SH-DR15-C

Shades supplied separately, see pg.162-164



victoria reader

- SH-WBVICR-AB ■
- SH-WBVICR-SN ■
- SH-WBVICR-MB ■



CLASS 1



SWITCH

Key Features

Matt black / Satin nickel /

Antique brass

E27 LED Max. 20W

Reading Arm

3000K

1W CREE Power LED / 90 lumens

E27 LED Max. 20W

90° pivot, 350° rotation

Replaceable LED 'MOD1W'



Shades supplied separately, see pg.162-164

fenchurch

SH-WBFEN-SN ■



CLASS 2



DIMMABLE



SWITCH

Key Features


Satin nickel

Steel

E27 LED Max. 20W

Swing arm, 2 x 180°


Removable pull cord



hotel wall lights







PAINTABLE

how to paint

All our plaster items are paintable. Follow these steps to achieve the best finish.

- ① seal the plaster with a PVA sealer (1 part PVA to 1 part water). allow to dry thoroughly
- ② paint with a soft brush. allow to dry
- ③ lightly sand
- ④ apply a second coat of paint with a soft brush

p this symbol represents a white plaster finish



PL-CONCO



PL-CONCO




PL-CONCO



PL-CONCS


concorde round

PL-CONCO 



concorde square

PL-CONCS 



CLASS 2



DIMMABLE



PAINTABLE

Key Features

White plaster

2 x Max. 10W GU10 LED

Paintable with a good quality emulsion paint




PL-EUROR



PL-EUROR

europa round

PL-EUROR  
450 lumens



CLASS 2



PAINTABLE

Key Features

White plaster

3000K

6W CREE COB LED

Paintable with a good quality
emulsion paint





PL-MIRAB



PL-MIRAB




PL-MONCE



PL-MONCE


mirabeau

PL-MIRAB 
470 lumens



monceau

PL-MONCE  ▲
470 lumens



CLASS 1



PAINTABLE

Key Features

White plaster

3000K

6W CREE COB LED

Paintable with a good quality
emulsion paint



PL-AVRON



PL-AVRON



PL-AVRON

avron

PL-AVRON 

600 lumens



CLASS 2



PAINTABLE

Key Features

White plaster

3000K

10W SMD LED

Paintable with a good quality

emulsion paint



PL-CADET




PL-CADET



PL-CADET

cadet

PL-CADET 
700 lumens



CLASS 2



PAINTABLE

Key Features

White plaster

3000K

9W SMD LED

Paintable with a good quality
emulsion paint



PL-CAMBR



PL-CAMBR




PL-CAMBR

cambronne

PL-CAMBR  

350 lumens



CLASS 2



PAINTABLE

Key Features

White plaster

3000K

9W SMD LED

Paintable with a good quality

emulsion paint



PL-OPERA



PL-ODEON




PL-OPERA

odeon

PL-ODEON 


11W SMD LED
610 lumens



opera

PL-OPERA  

3W POWER LED
175 lumens



CLASS 2



PAINTABLE

Key Features

White plaster

3000K

Paintable with a good quality
emulsion paint



For detailed drawings and specifications along with help & advice, visit www.projectcollection.co.uk

table & floor



New





TA-LIB2-B



FS-LIB2-B




TA-LIB2-W

libra 2 table

New


TA-LIB2-B ■
TA-LIB2-W □



libra 2 floor

New

FS-LIB2-B ■
FS-LIB2-W □



CLASS 2



SWITCH

Key Features

Sand black / Sand white

Die cast construction

GU10 max. 10W LED only

30° beam angle

For European plug use code:

EUTA-LIB2-**

EUFS-LIB2-**



TA-OLY-AB-USB & SH-DR30-C




TA-OLY-SN-USB

olympia table USB

TA-OLY-AB-USB ■ ▲

TA-OLY-SN-USB ■

With USB charging port



CLASS 2

SWITCH

USB

Key Features

Antique brass / Satin nickel

E27 max. 20W / LED only

Switch on base

For European plug use code:

EUTA-OLY-**

EUFS-OLY**



FS-OLY-SN & SH-DR40-M



TA-OLY-AB

FS-OLY-SN




Shades supplied separately, see pg.162-164

olympia table

- TA-OLY-AB ■ ▲
 - TA-OLY-SN ■
- Switch on base

olympia floor

- FS-OLY-AB ■ ▲
 - FS-OLY-SN ■
- In-line switch



CLASS 2



SWITCH

Key Features

Antique brass / Satin nickel

E27 max. 20W / LED only

Floor lamp has inline switch on cable

Table lamp has switch on base

For European plug use code:

EUTA-OLY-**

EUFS-OLY**





TA-KEN-SN



FS-KEN-SN



FS-KEN-SN


TA-KEN-SN



Shades supplied separately, see pg.162-164


kensington table

TA-KEN-SN



kensington floor

FS-KEN-SN



CLASS 2



SWITCH

Key Features

Satin nickel finish

E27 max. 20W

LED only

Inline switch on cable

For European plug use code:

EUTA-KEN-**


EUFS-KEN-**



shades



shades



Colour		Cone	Small Rectangle	Large Rectangle	Open Square	Drum 15	Drum 30	Drum 40
	Coconut	SH-CO-C	SH-RS-C	SH-RL-C	SH-SQO-C	SH-DR15-C	SH-DR30-C	SH-DR40-C
	Mushroom	SH-CO-M	SH-RS-M	SH-RL-M	SH-SQO-M	SH-DR15-M	SH-DR30-M	SH-DR40-M
	Grey Seal						SH-DR30-G	SH-DR40-G


Range	Page no.							
3lt Suspension	165							●
3lt Semi-flush	165							●
Pimlico 2	134-135	●	●	●	●	●		
Pimlico 2 Reader	136-137	●	●	●	●	●		
Victoria	138-139	●	●	●	●	●		
Fenchurch	140	●				●		
Kensington Table	158-159	●		●			●	
Kensington Floor	158-159			●				●
Olympia Table	156-157	●		●			●	
Olympia Floor	157							●

Key


- C - Coconut
- M - Mushroom
- G - Grey seal

All the shades in this collection are:
 White PVC lining
 To suit E27/E14/B22 shade ring
 For use with LED lamps only
 Available from stock in the UK
 Flame retardant

Shade material without light source



Shade material with 3000K light source




drum 15cm



SH-DR15-M

SH-DR15-C SH-DR15-M




drum 30cm



SH-DR30-G

SH-DR30-C SH-DR30-M
 SH-DR30-G




drum 40cm



SH-DR40-G

SH-DR40-C SH-DR40-M
 SH-DR40-G




diffuser



SH-DIF40

SH-DIF40




small rectangle



SH-RS-M

SH-RS-C SH-RS-M




large rectangle



SH-RL-G

SH-RL-C SH-RL-M




open square



SH-SQO-C

SH-SQO-C SH-SQO-M




cone



SH-CO-M

SH-CO-C SH-CO-M





SH-SF3-SN






SH-P3-SN

E27 3 light semi flush

SH-SF3-SN ■ ▲

E27 3 light suspension

SH-P3-SN ■ ▲



CLASS 1



DIMMABLE



TRACK ADAPTER

Key Features

E27 20W Max

1.8m Clear cable

LED only / 220-240V

IP20

Height adjustable

Suitable for:
Drum 30 & Drum 40 shades. Shades available in colours:
Grey seal / Coconut / Mushroom



Any outdoor product with this symbol is warranted for installation a minimum of 1km away from the coast





outdoor





IPR-EUSSS



IPR-EUSSS



IPR-HOODSS



IPR-HOODSS

euston 230V

IPR-EUSSS




420 lumens



CUT OUT
49mm



DRIVE OVER
2000kg



Installation tube



hood 230V

IPR-HOODSS



285 lumens



CUT OUT
49mm



CUT OUT
53mm



CLASS 1



IP
67




230 VOLTS



COASTAL
>1KM

Key Features

- Satin stainless steel Grade 316 cover / Passivated aluminium body
- 3000K
- 6W CREE COB LED
- Integral driver
- Includes installation tube
- Installation tube must be used for drive over applications



IP
67



DRIVE OVER
2000kg



700mA



COASTAL
>1KM

Key Features

Satin stainless steel Grade 316 cover /

Passivated aluminium body

3000K

3W CREE XPE Power LED

Driver supplied separately

Fittings must be wired in series

Dimmable when used with a dimmable
driver

Installation tube must be used for drive
over applications

Cut-out without installation tube: 36mm



IPR-PLOT4SS



IPR-PLOT3SS



IPR-PLOT2SS



IPR-PLOT1SS

Driver supplied separately, see pg. 220



IPR-PLOT4SS

IPR-PLOT1SS

4 way plot light

IPR-PLOT4SS
4 x 70° Beam

3 way plot light

IPR-PLOT3SS
3 x 70° Beam






2 way plot light

IPR-PLOT2SS
2 x 110° Beam

1 way plot light

IPR-PLOT1SS
1 x 110° Beam

Average 90 lumens



Body length: 59mm



IPR-PICRSS



IPR-PICRSS



IPR-PICRSS



Driver supplied separately, see pg. 220

piccadilly IP67



320kg
WALKOVER


IPR-PICRSS

220 lumens

20° beam



CUT OUT
36mm



CUT OUT
with installation tube
39mm



DIMMABLE



IP
67



700mA



COASTAL
>1KM

Key Features

Satin stainless steel Grade 316 cover /

Passivated aluminium body

3000K

3W CREE XPE Power LED

Driver supplied separately

Fittings must be wired in series

Dimmable when used with a dimmable driver

Includes installation tube



IPR-PADRSS15 / IPR-PADRSS30



IPR-PADSS15 / IPR-PADSS30



IPR-PADRSS15



Driver supplied separately, see pg. 220



IPR-PADSS15



30° Beam



15° Beam

paddington round IP67



320kg WALKOVER

IPR-PADRSS15

15° beam

IPR-PADRSS30


30° beam



CUT OUT 21mm



CUT OUT with installation tube 26mm



paddington square IP67



320kg WALKOVER

IPR-PADSS15

15° beam

IPR-PADSS30


30° beam



CUT OUT 21mm



CUT OUT with installation tube 26mm



DIMMABLE



IP 67



350mA



COASTAL >1KM

Key Features

Satin stainless steel Grade 316 cover /

Passivated aluminium body

3000K / 90 lumens

1W CREE XPE Power LED

Driver supplied separately

Fittings must be wired in series

Dimmable when used with a dimmable

driver

Includes installation tube




OD-FARR & OD-FPOLE

OD-FARR700

farrington
8W 230V

OD-FARR ■
230V / Class I
CREE COB
550 Lumens



farrington
8W 700mA

OD-FARR700 ■ ▲
700mA / Class III
550 Lumens

OD-FPOLE ■
300mm extension pole,
use 2 for a 600mm extension



Key Features

- Passivated black
- Aluminium
- 3000K
- 8W CREE COB LED
- Pre fitted with 24° reflector
- 10° reflector supplied in the box
- Compatible with OD-FPOLE

New



OD-FARP & 2 x OD-FPOLE



OD-FARP

farrington plus 230V


New

OD-FARP ■

1400 lumens

OD-FPOLE ■

300mm extension pole,
use 2 for a 600mm extension



OD-FARP



CLASS 1



IP 67



230 VOLTS



COASTAL >1KM

Key Features

Passivated black

Aluminium

3000K

14W CREE COB LED

25° beam angle

Compatible with OD-FPOLE

New



OD-BEA-G




OD-BEA-G

beaumont

New

OD-BEA-G
520 lumens



CLASS 1



IP
65



230 VOLTS



COASTAL
>1KM

Key Features


Graphite

Aluminium

3000K

5W Osram Power LED

Warrantied for installation up to
1km from the coast



OD-SAN80-G



outdoor

OD-SAN80-G

**sanderson
bollard**

OD-SAN80-G ■
700 lumens



CLASS 1



IP
54



230 VOLTS



COASTAL
>1KM

Key Features

Graphite

Aluminium

3000K

9W Osram SMD LED

Warrantied for installation up to
1 km from the coast



grosvenor bollard 80cm

OD-GRO80-G ■
600 lumens



grosvenor bollard 30cm

OD-GRO30-G ■
600 lumens



CLASS 1



IP 54



230 VOLTS



COASTAL >1KM

Key Features

Graphite

Aluminium

3000K

8W CREE COB LED

Warrantied for installation up to

1km from the coast



OD-GRO80-G



OD-GRO30-G



OD-GRO230-G



OD-GRO280-G




OD-GRO230-G

outdoor

grosvenor II bollard 80cm

OD-GRO280-G ■
660 lumens



grosvenor II bollard 30cm

OD-GRO230-G ■
660 lumens



CLASS 1



IP 65



230 VOLTS



COASTAL
>1KM

Key Features

Graphite

Aluminium

3000K

13W CREE COB LED

Warrantied for installation up to

1km from the coast



OD-CON-G



OD-CONP-G




OD-CON-G



OD-CONP-G

connaught


OD-CON-G ■
13W CREE COB LED
1000 Lumens



connaught plus

New

OD-CONP-G ■
28W CREE COB LED
2150 Lumens



CLASS 1



IP
65



230 VOLTS



COASTAL
>1KM

Key Features

Graphite

Aluminium

3000K

Warrantied for installation up to
1km from the coast



New

outdoor



OD-SAV-G




OD-LAN-G



OD-SAV-G

savoy

OD-SAV-G
700 lumens



CLASS 1



IP
65



230 VOLTS



COASTAL
>1KM

Key Features

Graphite

Aluminium

3000K

13W CREE Power LED

Warrantied for installation up to


1km from the coast

New



lanesborough

OD-LAN-G
1150 Lumens



OD-LAN-G



CLASS 1



IP
65



230 VOLTS



COASTAL
>1KM

Key Features

Graphite


Aluminium

3000K

13W CREE COB LED

Warrantied for installation up to

1km from the coast



New



OD-SAVP-G

OD-SAVP-G




OD-SAVP-G

savoy plus

OD-SAVP-G

1850 lumens

Narrow beam reaches up to 6m in each direction



New



CLASS 1



IP 65



230 VOLTS



COASTAL >1KM

Key Features

Graphite

Aluminium

3000K

18W Osram Power LED

Warrantied for installation up to

1km from the coast



OD-BER1-G



OD-BER1-G



OD-BER1-G

berkeley

OD-BER1-G
900 lumens



CLASS 1



IP 65



230 VOLTS



COASTAL >1KM

Key Features

Graphite



Aluminium

3000K

8W CREE COB LED

Warrantied for installation up to 1 km from the coast

Only to be fitted in the downward position, as shown on the here





Adjustable beam angles



OD-STR-G



OD-MAY-G



OD-STR-G



OD-MAY-G

strand adjustable

OD-STR-G
13W CREE LED
500 lumens

mayfair adjustable

OD-MAY-G
6W CREE LED
270 lumens



CLASS 1



IP 65



230 VOLTS



COASTAL >1KM

Key Features



Graphite

Aluminium

3000K

Warrantied for installation up to 1km from the coast

Adjustable shutters top and bottom to change the beam angles independently





simplon IP65

See Pg. 206-207 for all information including product codes and technical drawings

pyrenees IP65



Key Features

Aluminium body

1W CREE XPE LED

Wall mounted

350mA items require a separate driver



OD-TRA-B



OD-TRA-B



OD-TRA-W



New

trafalgar GU10

New

OD-TRA-B



OD-TRA-W



∅90



CLASS 1



IP
65



230 VOLTS

Key Features

Sand black / Sand white

Aluminium / Glass

GU10 max. 10W LED only



OD-KOBL



OD-KOBL




OD-KOBM

kobe large

OD-KOBL


21W SMD LED
1300 lumens



kobe medium

OD-KOBM

16W SMD LED
900 lumens



CLASS 2



IP
54



230 VOLTS



COASTAL

Key Features

Dark grey

PC / ABS Material

3000K

Corrosion resistant

Suitable for use in coastal areas

Wall or ceiling mounted



OD-KYOM



OD-KYOM



OD-KYOS

kyoto medium

OD-KYOM

21W SMD LED
1500 lumens

kyoto small

OD-KYOS

17W SMD LED
1000 lumens



CLASS 2



IP
54



230 VOLTS



COASTAL

Key Features

Dark grey



PC / ABS Material

3000K

Corrosion resistant

Suitable for use in coastal areas

Wall or ceiling mounted





OD-CHIBA



OD-CHIBA




Interchangable covers

chiba duo

OD-CHIBA

1050 lumens



CLASS 2



IP
54



230 VOLTS



COASTAL

Key Features

Dark grey

PC / ABS Material

3000K

13W SMD LED

Corrosion resistant

Suitable for use in coastal areas

Wall or ceiling mounted

Supplied with both covers in the box



OD-TOKYO




OD-TOKYO



OD-TOKYO

tokyo

OD-TOKYO
800 lumens



CLASS 2



IP
54



230 VOLTS



COASTAL

Key Features

Dark grey

PC / ABS Material

3000K

13W SMD LED

Corrosion resistant

Suitable for use in coastal areas

Wall or ceiling mounted




OD-YOK



OD-YOK

yokohama

OD-YOK ■
320 lumens



Key Features

Dark grey

PC / ABS Material

3000K

6W SMD LED

Corrosion resistant

Suitable for use in coastal areas

Surface mounted



OD-SAPS-GW



OD-SAPS-GW




OD-SAPS-GW

sapporo square

OD-SAPS-GW ■ / □

45 lumens



CLASS 2



IP
65



230 VOLTS



COASTAL

Key Features

Dark grey and white covers

supplied in the box

PC / ABS Material


3000K

1.1W SMD LED

Corrosion resistant

Suitable for use in coastal areas

Surface mounted



OD-SUZ-GW



OD-SAPL-GW

OD-SUZ-GW


sapporo long

OD-SAPL-GW ■ / □
 3.5W SMD LED
 265 lumens



suzuka slot

OD-SUZ-GW ■ / □
 3W SMD LED
 310 lumens



Key Features

Dark grey and white covers

supplied in the box

PC / ABS Material

3000K

Corrosion resistant

Suitable for use in coastal areas


Surface mounted



For detailed drawings and specifications along with help & advice, visit www.projectcollection.co.uk

bathroom





CLASS 2



DIMMABLE



IP 44



GLASS

Key Features

Sand white / Sand black

Aluminium

3 x GU10, max. 10W LED only

Ceiling / Wall mounted

350° Rotation

90° Pivot

SP-SEL3R-W



SP-SEL3L-W



SP-SEL3L-B



selene 3 round IP44





- SP-SEL3R-B
- SP-SEL3R-W

selene 3 long IP44



- SP-SEL3L-B
- SP-SEL3L-W






trafalgar

New

OD-TRA-B
OD-TRA-W



Key Features

- Sand black / Sand white
- Aluminium / Glass
- GU10 max. 10W LED only



FL-ADM40-W




FL-ADM40-W



FL-ADM30-W


andaman 40cm IP44

FL-ADM40-W
25W SMD LED
1200 lumens



andaman 30cm IP44

FL-ADM30-W
14W SMD LED
600 lumens



CLASS 2



DIMMABLE



IP
44



GLASS


Key Features

Clear glass / Matt white inner glass

Glass / Steel

3000K

Ceiling or wall mounted




FL-BAN35-B

FL-BAN23-B


**banda 35cm
IP44**

FL-BAN35-B ■
27W SMD LED
650 lumens



**banda 23cm
IP44**

FL-BAN23-B ■
14W SMD LED
350 lumens



- 
CLASS 2
- 
DIMMABLE
- 
IP 44
- 
GLASS

Key Features

- Matt white glass / Black
- Glass / Steel
- 3000K



CE-PER130

peri IP44


New

CE-PER130

1400 lumens at 3000K

1800 lumens at 4000K

1600 lumens at 5000K



CLASS 2



DIMMABLE



IP
54



CCT
3 COLOURS

▲ 3000K

▲ 4000K

▲ 5000K

Key Features

White

Polycarbonate

3000K / 4000K / 5000K switchable

CCT switch in body

17W SMD LED

Rear or side cable entry

Ceiling or wall mounted



3000K



4000K



5700K



CE-VER40-B

verve 30 IP44

New

CE-VER30-B



CE-VER30-W




16W SMD LED

1450 lumens at 3000K

1750 lumens at 4000K

1650 lumens at 5700K



verve 40 IP44

New

CE-VER40-B



CE-VER40-W




23W SMD LED

2100 lumens at 3000K

2300 lumens at 4000K

2100 lumens at 5700K



CLASS 2



DIMMABLE



IP 44



Key Features

Sand black / Sand white

Aluminium / PC diffuser

3000K / 4000K / 5700K

Switchable

Switch on back of fitting

Ceiling or wall mounted




IPR-WSLW

IPR-WSLB

Item no.	Finish	Power	CCT	Lumens	IP Rating	Dimmable	Replaceable LED module	Class
IPR-WSLB	■ Black	350mA	3000K	45	65	Yes*	MOD1WIP	III
IPR-WSLB-AC	■ Black	220 - 240V**	3000K	45	65	No	MOD1WIP230V	I
IPR-WSLB27	■ Black	350mA	2700K	45	65	Yes*	MOD1WIP-2700	III
IPR-WSLB27-AC	■ Black	220 - 240V**	2700K	45	65	No	MOD1WIP230V-2700	I
IPR-WSLW	□ White	350mA	3000K	95	65	Yes*	MOD1WIP	III
IPR-WSLW-AC	□ White	220 - 240V**	3000K	95	65	No	MOD1WIP230V	I
IPR-WSLW27	□ White	350mA	2700K	95	65	Yes*	MOD1WIP-2700	III
IPR-WSLW27-AC	□ White	220 - 240V**	2700K	95	65	No	MOD1WIP230V-2700	I

*Dimmable when used with a dimmable driver ** Integrated Driver

simplon IP65



Key Features

Sand white / Sand black

Aluminium

1W CREE XPE Power LED

30° beam angle

Mounting box included for solid wall applications



IPR-WRW

IPR-WRB


Item no.	Finish	Power	CCT	Lumens	IP Rating	Dimmable	Replaceable LED module	Class
IPR-WRB	■ Black	350mA	3000K	50	65	Yes*	MOD1WIP	III
IPR-WRB-AC	■ Black	220 - 240V**	3000K	50	65	No	MOD1WIP230V	I
IPR-WRB27	■ Black	350mA	2700K	50	65	Yes*	MOD1WIP-2700	III
IPR-WRB27-AC	■ Black	220 - 240V**	2700K	50	65	No	MOD1WIP230V-2700	I
IPR-WRW	□ White	350mA	3000K	95	65	Yes*	MOD1WIP	III
IPR-WRW-AC	□ White	220 - 240V**	3000K	95	65	No	MOD1WIP230V	I
IPR-WRW27	□ White	350mA	2700K	95	65	Yes*	MOD1WIP-2700	III
IPR-WRW27-AC	□ White	220 - 240V**	2700K	95	65	No	MOD1WIP230V-2700	I

*Dimmable when used with a dimmable driver ** Integrated Driver

pyrenees IP65



CUT OUT
60mm



Key Features

Sand white / Sand black

Aluminium

1W CREE XPE Power LED

30° beam angle


Mounting sleeve included for solid wall applications



holborn IP65

IPR-HOLSS


1W CREE XPE Power LED
90 lumens / 120° beam angle



hoxton IP65

IPR-HOXSS ▲ IPR-HOXCP

1W CREE XPE Power LED
90 lumens / 120° beam angle



CLASS 3



IP 65



DIMMABLE



350mA

Key Features

Polished chrome or satin
stainless steel 316 /
Aluminium body

3000K

Very shallow profile

Driver supplied separately

Fittings must be wired in series



IPR-HOLSS

holborn anti glare IP65



IPR-HOLSSAG



Key Features

Satin stainless steel 316

1W CREE XPE / 3000K

25 lumens / Beam angle: 120°


Very shallow profile

Driver supplied separately

Fittings must be wired in series



IPR-HOLSSAG



diana

DL-DIA-W



Key Features

Sand white finish / Die cast body

1W Olsen LED / 3000K


95 lumens / Beam angle: 30°

Driver supplied separately

Fittings must be wired in series



DL-DIA-W





IPR-PICRSS



IPR-PICRSS



IPR-PICRSS



Driver supplied separately, see pg. 220

piccadilly IP67




IPR-PICRSS

220 lumens

20° beam



CUT OUT
36mm



CUT OUT
with installation tube
39mm



DIMMABLE



IP
67



700mA



COASTAL
>1KM

Key Features

Satin stainless steel Grade 316 cover /

Passivated aluminium body

3000K

3W CREE XPE Power LED

Driver supplied separately

Fittings must be wired in series

Dimmable when used with a dimmable driver

Includes installation tube



Driver supplied separately, see pg. 220



paddington round IP67



IPR-PADRSS15

15° beam

IPR-PADRSS30


30° beam



CUT OUT 21mm



CUT OUT with installation tube 26mm



paddington square IP67



IPR-PADSSS15

15° beam

IPR-PADSSS30


30° beam



CUT OUT 21mm



CUT OUT with installation tube 26mm



Key Features

Satin stainless steel Grade 316 cover /

Passivated aluminium body

3000K / 90 lumens

1W CREE XPE Power LED

Driver supplied separately

Fittings must be wired in series

Dimmable when used with a dimmable

driver

Includes installation tube




glacier IP65

DL-GLAR ▲



CUT OUT
70mm



CLASS 2 DIMMABLE IP65

Key Features

Acrylic & Polished chrome

1 x GU10, max. 10W LED only



DL-SOPWB



DL-SOPWB



DL-SOPWB

sophie IP65

New


DL-SOPWB /



CUT OUT
65mm



MIN DEPTH
120mm



CLASS 2



DIMMABLE



IP
65

Key Features

Matt White

1 x GU10, max. 10W LED only

Suitable for indoor or
outdoor use

Comes with both black and white
covers in the box

Distance to front of lamp: 6mm



DL-SLIMFRW 🔥

slim trim
IP65 FR




DL-SLIMIPFRW □



CUT OUT
72mm



MIN DEPTH
120mm



DL-SLIMIPFRW 🔥💧



CLASS 1



DIMMABLE



IP
65

Key Features

Matt white

Steel

1 x GU10, max 10W LED only

Anti-glare

GU10 lampholder

Tested in 30, 60 and 90 minute
ceilings

Distance to front of lamp: 26mm



DL-SLIMIPW



DL-SLIMIPB

DL-SLIMIPW

slim trim IP65

DL-SLIMIPB ■



DL-SLIMIPW □



CUT OUT
70mm



MIN DEPTH
135mm



CLASS 2



DIMMABLE



IP
65

Key Features

Matt black / Matt white

Aluminium

1 x GU10, Max. 10W LED only

Lamp change from the front,
mounting sleeve remains in the
ceiling

Distance to front of lamp: 27mm



acqua

BA-M-ACQUA

19W SMD LED

1330 lumens



CLASS 2



SWITCH



IP 44



DE-MISTER

Key Features

Frosted / Mirrored glass

3000K

Removable pull cord

Demister pad heats the centre of the mirror when the light source is on



All bathroom lighting installations must comply to the guidelines set out in Amendment 1 of the 17th edition of the IEE Wiring Regulations (BS7671). The bathroom is divided into zones, with prescribed minimum IP ratings for the light fittings in each zone.

IP rating = Ingress Protection rating.

zone 0

The area inside the bath or shower tray. Fittings must be rated at IPX7 or higher (protected against immersion in water).

zone 1

The area above the bath or shower up to a height of 2.25 metres. Fittings must be rated at IPX5 or higher (protected from jets of water).

zone 2

Covers an area 0.6 metres wide immediately next to, and all around Zone 1. The 60cm area around washbasins should also be treated as zone 2. The minimum rating is IPX4. If there is a likelihood of water jets being used for cleaning purposes in Zone 2, a minimum of IPX5 is required.

outside zone

Covers any area outside Zones 0, 1 and 2. There is no IP requirement in this zone. Bathrooms are allowed to contain a socket outlet, this must be located 3 metres outside Zone 1. Lighting circuits and any socket-outlet circuit in a room containing a bath and/or shower must be provided with 30mA RCD protection.

guide to constant current LEDs

Constant current LED items can be identified because the operating power is quoted in milliamps (mA). Project Collection constant current items are either 350mA or 700mA.

Do I need a separate driver?

Yes, choose a 350mA or 700mA driver to suit the number of fittings you want to run, and whether you want to dim the item. Fittings must be wired in series.

Is this dimmable?

Yes, if used with a dimmable 350mA driver and a compatible dimmer.


How do I work out which driver I need?

Identify the current, 350mA or 700mA.
Note the wattage of each item, e.g 1W, 3W

item wattage x no. of items = total wattage
select your driver to suit your requirements

How do I wire this?

In series. See the drivers listed below, the product fitting instructions or the drawing below



* NOTE: All these drivers must be wired in series

The driver doesn't fit through the hole / where do I put the driver?

Drivers should be sited somewhere you can access them for maintenance. This can be up to 60m away from the furthest fitting.

The driver will often be larger than the hole cut out for the item. Again, locate it in another place, where you can access it in the future if required

troubleshooting

The first fitting lights up, the others don't come on

You have wired this in parallel (not in series). You will need to buy replacements for all but the first one.

These are not repairable.

All the fittings have failed

This is due to driver failure. Check that you have wired the circuit correctly, or the driver may fail again.

My fittings come on for a while, then they go off, and turn back on by themselves later

Your driver is overheating. Improve the air flow around it.

My fittings are all flashing

This is a driver issue. First check your driver is not overrun or under-run (i.e. within the minimum and maximum wattages). Otherwise it is a faulty driver.

The first fitting in the circuit stays on after the circuit is turned off

You have residual current in the circuit, or current leakage. Try changing the switch. If these are on a circuit with an intermediate switch it is almost impossible to prevent a small amount of current leakage.
troubleshooting

accessories



MOD1WIP

1w IP65 350mA LED module

1W CREE XPE 350mA
Beam angle: 30°
95 lumens

MOD1WIP

3000K ●

MOD1WIP-2700

2700K ●



MOD1WIP230V

1w IP65 230V LED module

1W CREE XPE 350mA
Beam angle: 30°
95 lumens

MOD1WIP230

3000K ●

MOD1WIP230V-2700

2700K ●



MOD1W

1w 350mA LED module

1W CREE XPE 350mA
Beam angle: 30°
95 lumens

MOD1W

3000K ●

MOD1W-2700

2700K ●

constant current drivers

Item no.	Current	Min. load	Max. load	TRIAC dimmable	IP Rating	Power factor	Dimensions L x W x H (mm)	Tails / Screw terminals
DR350-3	350mA	1W	3W	No	IP65	0.9	38 x 27 x 21	Tails
DR350-3TD	350mA	2W	3W	Yes	IP65	0.9	38 x 27 x 21	Tails
DR350-7	350mA	1W	7W	No	IP65	0.4	60 x 35 x 23	Tails
DR350-9TD	350mA	2W	9W	Yes	IP20	0.9	110 x 45 x 28	Screw terminals
DR350-18TD	350mA	10W	18W	Yes	IP20	0.9	165 x 52 x 25	Screw terminals
DR700-3	700mA	1W	3W	No	IP65	0.4	38 x 27 x 21	Tails
DR700-9	700mA	3W	9W	No	IP65	0.5	60 x 35 x 23	Tails
DR700-18TD	700mA	6W	18W	Yes	IP20	0.9	110 x 45 x 28	Screw terminals
DR700-36TD	700mA	20W	36W	Yes	IP20	0.9	165 x 52 x 25	Screw terminals

product name index

andaman IP44	36	honos	40-41	pendant adapter	89	track kit	90
andromeda ceiling	39	hood 230V	169	peri IP44	33, 204	trafalgar	189, 201
andromeda track	84	hoxton IP65	80, 208	perla	114	trocadero	71
apollo	43	ice	118	piccadilly	172, 210	vavin	128
ara	20	jupiter	99	pimlico (2)	134-135	verve IP44	30, 205
artemis	43	kensington	159	pimlico (2)		victoria	138
avron	148	kobe	190	reader	136-137	victoria LED	120-121
banda IP44	37,203	kyoto	191	plot	171	victoria reader	139
beaumont	176	lanesborough	183	polo	49	vistina long	17
berkeley	185	large rectangle	164	pyrenees IP65	78, 207	vistina round	15
blackfriars	112	laser track	87	pyrenees plaster	73	vulcan	29
blanche GU10	76	laser pendant	13	ripple	32	wall washers	52-53
blanche LED	75	laser reader	115	rome	70	yokohama	195
boulogne LED	75	laser spot	92	sablons	67		
cadet	149	LED strip	102-104	sanderson	177		
cambronne	150	LED strip drivers	109	sapporo	196-197		
chiba duo	192	LED strip profile	107	saturn	34		
clip	28	libra track	86	savoy	182		
compass 2	25	libra 2	155	savoy plus	184		
concorde	144	lino 2	18	selene IP44	93, 200		
cone	163	london bridge	131	shades	162-164		
connaught	180	lyra	42	shoreditch	126		
dalston	117	marlow	116	simplon IP65	77, 206		
diana	81, 209	marylebone	119	simplon plaster	73		
drum	163	mayfair adjustable	187	slim trim	58-61		
E27 3 light	165	mini	51	slim trimless	64-65		
eternity 55	27	mini projector	123	sloane	124-125		
eternity 78	26	mirabeau	147	small rectangle	164		
europe round	145	monceau	147	sophie IP65	63,213		
euston 230V	169	moon	95-97	southwark	127		
farringdon	174-175	moon recessed	47	strand adjustable	187		
fenchurch	140	odeon	151	suzuka slot	197		
glacier	62, 212	olympia	156-157	swivel	39		
grid	54-57	open square	164	taurus track	85		
grosvenor	178	opera	151	tokyo	193		
grosvenor II	179	orbit 120cm	23	track	90		
halkin	133	orcus	35	track accessories	91		
holborn anti glare	81,209	orion track	86	track adapter	89		
holborn IP65	80,208	paddington	173, 211	track heads	84-87		

product code index

AM-VUL	29	FS-OLY	157	OD-SAV-G	182	PL-ROM	70
BA-M-ACQUA	216	IPR-EUSSS	169	OD-SAVP-G	184	PL-SAB	67
CE-AND	39	IPR-HOLSS	80, 208	OD-STR-G	187	PL-SIMPL	72
CE-HONR	41	IPR-HOLSSAG	81, 209	OD-SUZ-GW	197	PL-SLIMFRW	65
CE-HONSQ2	40	IPR-HOODSS	169	OD-TOKYO	193	PL-SLIMIPW	64
CE-HONSQ	41	IPR-HOXCP	80, 208	OD-TRA	189, 201	PL-SLIMW	64
CE-LINO2	18	IPR-PAD	173, 211	OD-YOK	195	PL-TROCA	71
CE-ORC40	35	IPR-PICRSS	172, 210	PA-VER	30	SH-CO	164
CE-PERI30	33	IPR-PLOT	171	PE-APO	43	SH-DIF40	163
CE-SWI	39	IPR-WR	78, 207	PE-ARA	20	SH-DR15	163
CE-VER	30, 205	IPR-WSL	77, 206	PE-ART	43	SH-DR30	163
DL-DIA-W	81, 209	LED-PROJ1W	123	PE-CLIP	28	SH-DR40	163
DL-GLAR	62, 212	LST-14	104	PE-COM2	25	SH-P3-SN	165
DL-GRID1	54	LST-4	102	PE-ETE55	27	SH-RL	164
DL-GRID1FR	56	LST-5	102	PE-ETE78	26	SH-RS	164
DL-GRID2	55	LST-CON1	105	PE-LAS6	13	SH-SF3-SN	165
DL-GRID2FR	56	LST-CON2	105	PE-LYRAB	42	SH-SQO	164
DL-GRID3	55	LST-CON3	103	PE-ORB120	23	SH-VICLED	120-121
DL-MINW	51	LST-CON4	103	PE-VIST	17	SH-WBFEN-SN	140
DL-POLW	49	LST-DR	108-109	PE-VISTR	15	SH-WBPIM	134-137
DL-SLIM	59	LST-PRO	106-107	PL-AVRON	148	SH-WBVIC	138-139
DL-SLIMFRW	58	OD-BEA-G	176	PL-BLA	75	SP-JUP	99
DL-SLIMIP	61, 215	OD-BER1-G	185	PL-BLAGU10	76	SP-LAS1S	92
DL-SLIMIPFR	60, 214	OD-CHIBA	192	PL-BOU	74	SP-MOO1	95
DL-SLIMSQ	59	OD-CON	180-181	PL-CADET	149	SP-MOO1R	95
DL-SOPWB	63, 213	OD-FARP	175	PL-CAMBR	150	SP-MOO1S	95
DL-WASH	53	OD-FARR	174	PL-CONC	144	SP-MOO2	97
DL-WWW	52	OD-FPOLE	174	PL-EUROR	145	SP-MOO3	96
FL-ADM	36, 202	OD-GRO	178-179	PL-GRID1FR	57	SP-MOO3L	96
FL-BAN	37, 203	OD-KOB	190	PL-MINW	51	SP-MOO4	97
FL-ETE55-WS	27	OD-KYO	191	PL-MIRAB	147	SP-MOOR	47
FL-LYRAB	42	OD-LAN-G	183	PL-MONCE	147	SP-SEL3	93, 200
FL-RPL40	32	OD-MAY-G	187	PL-ODEON	151	TA-KEN	159
FL-SAT	34	OD-SAN80-G	177	PL-OPERA	151	TA-LIB2	155
FS-KEN	159	OD-SAPL-GW	197	PL-POLW	49	TA-OLY	157
FS-LIB2	155	OD-SAPS-GW	196	PL-PYREN	72	TA-OLY-USB	156

TR-1	90
TR-2	90
TR-AND	84
TR-CC	91
TR-EC	91
TR-FC	91
TR-LAS	87
TR-LC	91
TR-LE	91
TR-LIB	86
TR-MJ	91
TR-ORI	86
TR-PEN	89
TR-SUS	91
TR-T1	90
TR-T2	90
TR-TAU	85
TR-TC	91
TR-XC	91
WL-BLF	112
WL-DAL	117
WL-HALK	133
WL-ICE	118
WL-LASR	115
WL-LB	131
WL-MAR	119
WL-MLW	116
WL-PRL	114
WL-SHO20	127
WL-SLO	124-125
WL-SOU24	126
WL-VAV	128

Additional information

Any typographical, clerical or other error or omission in any sales literature, quotation, price list, acceptance of offer, invoice or other document or information issued by the Company shall be subject to correction without any liability on the part of the Company. Goods supplied may vary in detail from the illustrations, drawings, measurements and descriptions set out in the Company's sales literature, which are approximate and for guidance only and will not form part of the Contract. Colour finishes will be maintained as accurately as possible but matching cannot be guaranteed. All terminology used in the Company's sales literature is, subject to these Conditions, that as understood by general usage in the trade. For full terms and conditions of sale consult your distributor.

guide to symbols

Products with this icon are limited stock items.



CLASS 1

Class I fittings must have their chassis connected to an electrical earth (ground).



CLASS 2

Class II or double insulated electrical fittings does not require a safety connection to electrical earth (ground).



CLASS 3

Class III fittings are designed to be supplied from a separated / safety extra-low voltage (SELV) power source.



IP 44

(4) Objects greater than 1 mm, e.g. tools, wires / small wires
(4) Protected against water sprayed from all directions - limited ingress permitted.



IP 54

(5) Protected against dust - limited ingress (no harmful deposits)
(4) Protected against water sprayed from all directions - limited ingress permitted.



IP 65

(6) Totally protected against dust (Dust-tight)
(5) Protected against low pressure jets of water from all directions - limited ingress permitted.



IP 67

(6) Totally protected against dust (Dust-tight)
(7) Protection against the effects of immersion between 15cm - 1 metre



SWITCH

The product has an electrical ON/OFF switch incorporating a spring-loaded rocker.



DIMMABLE

The fitting can be used with a compatible dimming light switch.



GLASS

The fitting contains fragile glass parts.



CUT OUT 75mm

The fitting requires a ceiling or wall cut out.



DRIVE OVER

The outdoor, inset floor mounted fitting can be driven over by a vehicle, up to 2000kg weight limit.



FIRE RATED

Fire rated downlights restore the fire integrity of a ceiling with recessed ceiling lights installed.



320kg WALKOVER

The outdoor, inset floor mounted fitting can be walked over by a flat foot, up to 320kg weight limit.



350mA

A unit of electric current (mA) equal to one thousandth of an Amp.





24 VOLTS

The SI unit of electromotive force, the Volt (V) is a standard for extra low voltage power systems.

shade colours



C

Coconut colour cotton material lamp shade.




M

Mushroom colour cotton material lamp shade.



G

Grey seal colour cotton material lamp shade.



fitting finishes



AB

Antique brass finish for fixtures & fittings.



SN

Satin nickel finish for fixtures & fittings.



CP

Polished chrome finish for fixtures & fittings.



B

Black finish for fixtures & fittings.




W

White finish for fixtures & fittings.




GR


Graphite grey finish for fixtures & fittings.




Antique brass



Satin nickel



Polished chrome



Black



















White



Graphite grey













gids voor symbolen

 <p>KLASSE 1</p> <p>Klasse 1 armaturen moeten in bezit zijn van een aardeverbinding.</p>	 <p>KLASSE 2</p> <p>Klasse 2 armaturen hoeven geen aardeverbinding te bezitten.</p>	 <p>KLASSE 3</p> <p>Klasse 3 armaturen zijn ontworpen voor een externe laagspanningsvoeding.</p>	 <p>IP 44</p> <p>IP44 (4) Objecten groter dan 1mm zoals bv kabels / armaturen zijn (4) beschermd tegen water nevel vanuit elke hoek. Beperkt indringen toegestaan.</p>	 <p>IP 54</p> <p>IP55 (5) Beschermd tegen stof - beperkt indringen toegestaan en niet schadelijk. (5) Beschermd tegen water nevel vanuit elke hoek. Beperkt indringen toegestaan.</p>	 <p>IP 65</p> <p>IP65 (6) Compleet beschermd tegen stof (5) Beschermd tegen lichte waterstralen, vanuit elke hoek. Beperkt indringen toegestaan.</p>	 <p>IP 67</p> <p>IP67 (6) Compleet beschermd tegen stof (7) Beschermd tegen het effect van onderdompeling 15cm tot 1m.</p>	 <p>SCHAKELAAR</p> <p>Dit product heeft een elektrische aan/uit schakelaar, in combinatie met een veerbelaste tuimelaar.</p>
 <p>DIMBAAR</p> <p>Dit armatuur is geschikt om te dimmen, in combinatie met dimbare lichtbron.</p>	 <p>GLAS</p> <p>Dit armatuur bevat kwetsbare glazen onderdelen.</p>	 <p>OPENING 75mm</p> <p>Voor dit armatuur is een opening in het plafond vereist.</p>	 <p>OVERRIJBAAR</p> <p>Geschikt voor plaatsing in de vloer, met een drukbelasting tot 2000 kilo.</p>	 <p>BRÄNDWER-END</p> <p>Dit armatuur beschikt over een brandwerende functie.</p>	 <p>320kg OVERLOOP-BAAR</p> <p>Geschikt voor plaatsing in de vloer, met een drukbelasting tot 320 kilo.</p>	 <p>350mA</p> <p>Een eenheid van elektrische stroom gelijk aan een duizendste van een Amp.</p>	 <p>24 VOLTS</p> <p>De SI-eenheid van elektromotorische kracht, is volt. Dit is standaard voor extra laagspanningssystemen.</p>

















lampenkappen kleuren

<p>C</p> <p>Coconut kleur katoen materiaal lampenkap.</p>	<p>M</p> <p>Mushroom kleur katoen materiaal lampenkap.</p>	<p>G</p> <p>Grey seal kleur katoen materiaal lampenkap.</p>
 <p>Coconut UIT</p>	 <p>Coconut ANN</p>	 <p>Mushroom UIT</p>
 <p>Mushroom ANN</p>	 <p>Grey seal UIT</p>	 <p>Grey seal ANN</p>

armatuur kleuren

 <p>AB</p> <p>Antiek messing afwerking voor armaturen en fittingen.</p>	 <p>SN</p> <p>Satijn messing afwerking voor armaturen en fittingen.</p>	 <p>CP</p> <p>Geopolijst messing afwerking voor armaturen en fittingen.</p>	 <p>B</p> <p>Zwart messing afwerking voor armaturen en fittingen.</p>	 <p>W</p> <p>Wit messing afwerking voor armaturen en fittingen.</p>	 <p>GR</p> <p>Grafiet messing afwerking voor armaturen en fittingen.</p>
 <p>Antique brass</p>	 <p>Satin nickel</p>	 <p>Polished chrome</p>	 <p>Black</p>	 <p>White</p>	 <p>Graphite grey</p>

guide des symboles

 <p>CLASSE 1</p> <p>Dispositifs de Classe I : Le châssis doit être connecté à une prise de terre.</p>	 <p>CLASSE 2</p> <p>Classe II ou double isolation du câblage électrique connexion de sécurité à une prise de terre électrique non obligatoire.</p>	 <p>CLASSE 3</p> <p>Les dispositifs de classe III sont conçus pour être alimentés par une source d'alimentation séparée en basse tension (SELV).</p>	 <p>IP 44</p> <p>(4) Protégé contre objets de plus de 1 mm, exemple : outils, fils électriques (4) Protégé contre l'eau pulvérisée dans toutes les directions - pénétration limitée.</p>	 <p>IP 54</p> <p>(5) Protégé contre la poussière - pénétration limitée (pas de dépôts) (4) Protégé contre l'eau pulvérisée dans toutes les directions - pénétration limitée.</p>	 <p>IP 65</p> <p>(6) Totalemment protégé contre la poussière (étanche à la poussière) (5) Protégé contre les jets basse pression dans toutes les directions - pénétration limitée.</p>	 <p>IP 67</p> <p>(6) Totalemment protégé contre la poussière (étanche à la poussière) (7) Protection contre les effets de l'immersion entre 15cm - 1 mètre.</p>	 <p>INTER</p> <p>Le produit possède un interrupteur électrique interrupteur ON/OFF incorporant une bascule à ressort.</p>
 <p>DIMMABLE</p> <p>Le dispositif peut être utilisé avec un appareil variateur de lumière compatible.</p>	 <p>VERRES</p> <p>The fitting contains fragile glass parts.</p>	 <p>DÉCOUPE 75mm</p> <p>L'installation électrique de l'appareil nécessitent une découpe.</p>	 <p>DRIVE OVER</p> <p>L'encastré de sol peut être écrasé par un véhicule, jusqu'à une limite de poids de 2000 kg.</p>	 <p>FIRE RATED</p> <p>Ignifuge - Protection au feu - prévient le risque d'incendie dans un plafond.</p>	 <p>320kg WALKOVER</p> <p>L'armature de l'encastrée de sol résiste jusqu'à un poids de 320 kg.</p>	 <p>350mA</p> <p>Unité de courant électrique (mA) égale à un millième d'ampère.</p>	 <p>24 VOLTS</p> <p>L'unité SI de la force électromoteur, le Volt (V) est un standard pour les puissances basse tension.</p>

couleurs abajour

<p>C</p> <p>Coconut Abat-jour en coton de couleur.</p>	<p>M</p> <p>Mushroom Abat-jour en coton de couleur.</p>	<p>G</p> <p>Grey seal Abat-jour en coton de couleur.</p>
 <p>Coconut OFF</p>	 <p>Coconut ON</p>	 <p>Mushroom OFF</p>
 <p>Mushroom ON</p>	 <p>Grey seal OFF</p>	 <p>Grey seal ON</p>

finitions des luminaires

 <p>AB</p> <p>Finition en laiton antique pour les luminaires et les composants.</p>	 <p>SN</p> <p>Finition en Nickel Satiné pour les luminaires et les composants.</p>	 <p>CP</p> <p>Finition en Chrome Poli pour les luminaires et les composants.</p>	 <p>B</p> <p>Finition en Noir pour les luminaires et les composants.</p>	 <p>W</p> <p>Finition en Blanc pour les luminaires et les composants.</p>	 <p>GR</p> <p>Finition en Gris graphite pour les luminaires et les composants.</p>
 <p>Laiton antique</p>	 <p>Nickel satiné</p>	 <p>Chrome poli</p>	 <p>Noir</p>	 <p>Blanc</p>	 <p>Gris graphite</p>



project collection

www.projectcollection.co.uk

2024

Netherlands Showroom / Office

Searchlight Electric Ltd

Hoogjens 1

4254 XV Sleeuwijk

Netherlands

+31 85-303 6527

European Warehouse

Searchlight Electric / Clipper

Logistics Starachowicka 16

Number 9

62-023 Robakowo

Polen

Contact us:

international@searchlightelectric.com

Germany Office

Mainz: +49 6131 276 3003

France Office

Lyon: +33 4 87 94 03 47

Sweden Office

Stockholm: +46 8 121 607 51

Searchlight Electric Ltd

UK & Ireland

Sidney House

900 Oldham Road

Manchester

M40 2BS

United Kingdom

UK Office

Manchester: +44 (0) 161 203 3456

info@projectcollection.co.uk

sales@searchlightelectric.com



+44 (0) 161 203 3456

info@projectcollection.co.uk

